

2008 TransPac Monohull Check List

Date:			
Inspector:			
Skipper:			
Boat Name:			
Boat Number:			
Sail Number:			
Boat Location:			
PHRF:	Certificate matches boat.		YES NO
If Not - Note			
Anchor:	Suitable Anchor AND Rode.	4.15	YES NO
Batteries:	Minimum of two with at least combined 120aH capacity AND	4.21	YES NO
	Batteries: Charging system allowing batteries to be used during the period of darkness each day.	4.22	YES NO
Berth:	Fixed and suitable for sleeping in prone position at sea.	4.41	YES NO
Bilge Pumps:	Fixed mount, manual, operable above decks, capable of 10gpm discharge AND	4.14	YES NO
	Secondary manual OR electric.		YES NO
Bucket:	Stout construction with at least 2 US gallons capacity AND a lanyard.	4.39	YES NO
Charts:	18022 edition #35 19004 edition #38 19381 edition #8 #530 edition #32	4.27	YES NO
Cockpit:	Structurally sound AND self draining at all angles of heel.	4.2	YES NO

Companionway hatch boards:	Shall be capable of being secured in position with hatch open or shut and shall be secured to the boat with a lanyard AND	4.37	<input type="checkbox"/> YES <input type="checkbox"/> NO
	The Hatch shall be able to be secured in position by the skipper whether inside the boat, or on deck.		<input type="checkbox"/> YES <input type="checkbox"/> NO
Compass:	Properly installed mechanical marine compass with deviation card AND	4.26	<input type="checkbox"/> YES <input type="checkbox"/> NO
	A spare mechanical compass.		<input type="checkbox"/> YES <input type="checkbox"/> NO
Depth Sounder:	Functioning electronic or Lead Line	4.28	<input type="checkbox"/> YES <input type="checkbox"/> NO
EPIRB:	Transmits on 406.0 MHz with a battery with expiration date no earlier than August 3, 2008	4.35	<input type="checkbox"/> YES <input type="checkbox"/> NO
	Serial Number:		
Fire Extinguishers:	At Coast Guard required levels.	4.13	<input type="checkbox"/> YES <input type="checkbox"/> NO
First Aid Kit:	Accessible with manual	4.17	<input type="checkbox"/> YES <input type="checkbox"/> NO
Flashlights:	At least two with spare batteries AND bulbs. Waterproof.	4.16	<input type="checkbox"/> YES <input type="checkbox"/> NO
Flares:	It is strongly recommended, though not required by the NOR, that flares contained in the packed life raft are not included in the required number of flares carried aboard. The expiration date on each flare must be no earlier than Aug. 3, 2008. As specified in 4.36(f) 4 SOLAS Red parachute flares 4 SOLAS Red hand flares 2 SOLAS Orange smoke flares	4.36	<input type="checkbox"/> YES <input type="checkbox"/> NO
Fuel Tanks:	Have shut off valves.	4.38	<input type="checkbox"/> YES <input type="checkbox"/> NO
Food:	Enough for 30 days (Only needs to be present for final inspection)	4.10	<input type="checkbox"/> YES <input type="checkbox"/> NO
Galley:	Suitable for use at Sea.	4.9	<input type="checkbox"/> YES <input type="checkbox"/> NO
GPS:	Two operable units, with one operable as independent from the boat.	4.30	<input type="checkbox"/> YES <input type="checkbox"/> NO

Halyards:	At least two capable of raising sails.	4.40	<input type="checkbox"/> YES <input type="checkbox"/> NO
Horn:	Manual and operable.	4.18	<input type="checkbox"/> YES <input type="checkbox"/> NO
Jackstays:	Present both Starboard AND Port AND	4.6	<input type="checkbox"/> YES <input type="checkbox"/> NO
	Secured to through bolted attachment points AND		<input type="checkbox"/> YES <input type="checkbox"/> NO
	Rated for 4,500#'s or greater.		<input type="checkbox"/> YES <input type="checkbox"/> NO
Knot meter:	Functioning electronic or Log	4.29	<input type="checkbox"/> YES <input type="checkbox"/> NO
Length of deck	Between 20' and 60'	NOR	<input type="checkbox"/> YES <input type="checkbox"/> NO
Lifelines:	Multi-strand stainless steel wire enclosing the working deck AND	4.5	<input type="checkbox"/> YES <input type="checkbox"/> NO
	Height of at least 18" for boats less than 28' LOA. Height of at least 24" for boats greater than 28' LOA AND		<input type="checkbox"/> YES <input type="checkbox"/> NO
	Stanchions AND pulpits supporting lifelines not more than 7' apart AND properly secured.		<input type="checkbox"/> YES <input type="checkbox"/> NO
Life raft:	Automatically deployed canopy AND	4.36	<input type="checkbox"/> YES <input type="checkbox"/> NO
	Highly visible color AND		<input type="checkbox"/> YES <input type="checkbox"/> NO
	Stowed securely on deck OR		<input type="checkbox"/> YES <input type="checkbox"/> NO
	In a watertight, self draining compartment opening immediately to the working deck OR packed in a valise not exceeding 88#s, securely stowed below deck adjacent to the companionway AND		<input type="checkbox"/> YES <input type="checkbox"/> NO
	Valid annual inspection certificate. The certificate shall be dated no earlier than Aug. 3, 2008 AND		<input type="checkbox"/> YES <input type="checkbox"/> NO
	Sea Anchor, flashlight, knife, bailer, AND 4 days food and water		<input type="checkbox"/> YES <input type="checkbox"/> NO
	Repair kit, inflation pump and oral inflation tube AND Flares as required		<input type="checkbox"/> YES <input type="checkbox"/> NO
	15 second launch		<input type="checkbox"/> YES <input type="checkbox"/> NO
Serial Number:			
PFD:	Marked with Boat Name AND whistle	4.8	<input type="checkbox"/> YES <input type="checkbox"/> NO

	AND strobe attached.		
Plotting Instruments:	Onboard.	4.27	<input type="checkbox"/> YES <input type="checkbox"/> NO
Radar Reflector:	Mounted 13' above water AND	4.19	<input type="checkbox"/> YES <input type="checkbox"/> NO
	Octahedral must be 12" minimum diagonal OR		<input type="checkbox"/> YES <input type="checkbox"/> NO
	Otherwise Radar Cross Section (RCS) of not less than 1.5 meter squared over 20 degrees of heel.		<input type="checkbox"/> YES <input type="checkbox"/> NO
Race Numbers	Distinguishing numbers on each side AND	8	<input type="checkbox"/> YES <input type="checkbox"/> NO
	The greater of a height 12" of 1/40th the boat's LOA AND		<input type="checkbox"/> YES <input type="checkbox"/> NO
	Must be applied so as to prevent removal from the action of the sea.		<input type="checkbox"/> YES <input type="checkbox"/> NO
Running Lights:	Per COLREGS and above deck.	4.20	<input type="checkbox"/> YES <input type="checkbox"/> NO
Rubbish Storage	Recyclable and non-recyclable	4.12	<input type="checkbox"/> YES <input type="checkbox"/> NO
Safety Harness:	Minimum 3,300# breaking strength AND	4.7	<input type="checkbox"/> YES <input type="checkbox"/> NO
	Tether with breaking strength of 4,500 pounds and has a quick release snap shackle		<input type="checkbox"/> YES <input type="checkbox"/> NO
Sail Repair Kit:	Onboard.	4.34	<input type="checkbox"/> YES <input type="checkbox"/> NO
Sea cocks:	For those below the waterline softwood plugs for each attached with a line.	4.4	<input type="checkbox"/> YES <input type="checkbox"/> NO
Spotlight	Bright enough to illuminate sails	4.25	<input type="checkbox"/> YES <input type="checkbox"/> NO
SSB: or E-mail or sat. phone	That operates on 4, 8 AND 12 MHz bands. Radio must still be operable if dismasted OR E-mail	6.1	<input type="checkbox"/> YES <input type="checkbox"/> NO
Steering:	An alternative means of steering the boat in ANY sea condition AND	4.33	<input type="checkbox"/> YES <input type="checkbox"/> NO
	Demonstrated.		<input type="checkbox"/> YES <input type="checkbox"/> NO

Storm Sails:	A storm trysail capable of being sheeted independently of the boom AND of area not greater than 17.5% mainsail luff length x mainsail foot length. It shall have neither a headboard nor battens. A method of attaching the trysail to the mast shall be provided. The yacht's sail number and letter(s) shall be placed on both sides of the trysail in as large a size as is practicable. OR	4.42	<input type="checkbox"/> YES <input type="checkbox"/> NO
	Mainsail reefing to reduce luff length by at least 40%, but which does not obscure the appearance of the yacht's sail numbers.		<input type="checkbox"/> YES <input type="checkbox"/> NO
	If the rig such that a headsail is commonly used, then a storm sail shall be provided which attaches to a stay by a strong and secure method, AND is of an area not greater than 5% of the height of the fore triangle, squared and has a luff of maximum length of 65% of the height of the fore triangle.		<input type="checkbox"/> YES <input type="checkbox"/> NO
Strobe:	Mounted at masthead. Xenon bulb	4.24	<input type="checkbox"/> YES <input type="checkbox"/> NO
Tiller:	Emergency tiller capable of being fitted to rudder stock.	4.32	<input type="checkbox"/> YES <input type="checkbox"/> NO
Tools:	Including a way to disconnect or sever the standing rigging from the hull.	4.31	<input type="checkbox"/> YES <input type="checkbox"/> NO
VHF Radio:	25 watts output power and channels 6, 16 and 69 AND	4.23	<input type="checkbox"/> YES <input type="checkbox"/> NO
	Masthead antenna AND		<input type="checkbox"/> YES <input type="checkbox"/> NO
	Emergency antenna.		<input type="checkbox"/> YES <input type="checkbox"/> NO
Water Ballast:	Present AND	3.2	<input type="checkbox"/> YES <input type="checkbox"/> NO
	Below decks AND		<input type="checkbox"/> YES <input type="checkbox"/> NO
	Properly functions at 50 degrees of heel AND		<input type="checkbox"/> YES <input type="checkbox"/> NO
	Boat heels no more than 10 degrees with water on one side.		<input type="checkbox"/> YES <input type="checkbox"/> NO

Water Containers:	Securely installed AND	4.11	<input type="checkbox"/> YES <input type="checkbox"/> NO
	21 gallons OR more capacity in at least two containers.		<input type="checkbox"/> YES <input type="checkbox"/> NO
Whisker Poles:	No more than two AND	3.1	<input type="checkbox"/> YES <input type="checkbox"/> NO
	Cannot exceed LP of the largest rated headsail.		<input type="checkbox"/> YES <input type="checkbox"/> NO
Windows:	Require coverings if greater than 2 sq. ft. unless they are stronger than superstructure.	4.3	<input type="checkbox"/> YES <input type="checkbox"/> NO
Notes:			